P-Channel Enhancement Mode Power MOSFET

Description

The G020P04TA uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.

General Features

- V_{DS} -40V
- I_D (at V_{GS} = -10V) -360A
- $R_{DS(ON)}$ (at V_{GS} = -10V) < 2.2mΩ
- $R_{DS(ON)}$ (at V_{GS} = -4.5V) < 3.8mΩ
- 100% Avalanche Tested
- RoHS Compliant

Application

- Power switch
- DC/DC converters



Schematic diagram



TO-220

PRELIMINARY

Ordering Information

Device	Package	Marking	Packaging
G020P04TA	TO-220	G020P04	50pcs/Tube

Absolute Maximum Ratings T_C = 25ºC, unless otherwise noted

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V_{DS}	-40	V
Continuous Drain Current	T_C = 25ºC	I_D	-360	A
	T_C = 100ºC		-228	
Pulsed Drain Current (note1)		I_{DM}	-1440	A
Gate-Source Voltage		V_{GS}	±20	V
Power Dissipation		P_D	356	W
Single pulse avalanche energy （note2）		E_{AS}	625	mJ
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 To 150	ºC

Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	50	ºC/W
Maximum Junction-to-Case	R_{thJC}	0.35	ºC/W

Specifications T_J = 25ºC, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = -250μA	-40	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -40V, V_{GS} = 0V	--	--	-1	μA
Gate-Source Leakage	I_{GSS}	V_{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250μA	-1.0	-1.7	-2.5	V
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS} = -10V, I_D = -80A	--	1.9	2.2	mΩ
		V_{GS} = -4.5V, I_D = -80A	--	2.5	3.8	
Forward Transconductance	g_{FS}	V_{DS} = -5V,I_D = -80A	--	87	--	S
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -20V, f = 0.3MHz	--	28041	--	pF
Output Capacitance	C_{oss}		--	2681	--	
Reverse Transfer Capacitance	C_{rss}		--	2454	--	
Total Gate Charge	Q_g	V_{DD} = -20V, I_D = -80A, V_{GS} = -10V	--	412	--	nC
Gate-Source Charge	Q_{gs}		--	82	--	
Gate-Drain Charge	Q_{gd}		--	52	--	
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = -20V, I_D = -80A, R_G = 1.6Ω	--	88	--	ns
Turn-on Rise Time	t_r		--	98	--	
Turn-off Delay Time	$t_{d(off)}$		--	276	--	
Turn-off Fall Time	t_f		--	88	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	T_C = 25ºC	--	--	-360	A
Body Diode Voltage	V_{SD}	T_J = 25ºC, I_{SD} = -80A, V_{GS} = 0V	--	--	-1.2	V
Reverse Recovery Charge	Q_{rr}	I_F = -80A, V_{GS} = 0V di/dt=-100A/us	--	396	--	nC
Reverse Recovery Time	T_{rr}		--	154	--	ns

PRELIMINARY

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition : Tj=25℃ ,VDD=-40V,VGS=-10V,L=0.5mH,Rg=25Ω
   The table shows the minimum avalanche energy, which is 3969mJ when the device is tested until failure
3. Identical low side and high side switch with identical R_G

Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



PRELIMINARY

Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3.Drain Source On Resistance



Figure 4. Gate Charge



Figure 5. Capacitance



Figure 6. Source-Drain Diode Forward



PRELIMINARY

Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 7. Drain-Source On-Resistance



Figure 8. Safe Operation Area



Figure 9. Maximum Continuous Drain Current vs Case Temperature



Figure 10. Normalized Maximum Transient Thermal Impedance



PRELIMINARY

TO-220 Package Information



TOP VIEW SIDE VIEW(Right) BOTTOM VIEW



TOP VIEW(Front) SECTION:C-C SECTION:D-D

PRELIMINARY

DIM / SYMBOL	MIN.	NOM.	MAX.	DIM / SYMBOL	MIN.	NOM.	MAX.
A	4.450	4.550	4.650	D2	12.610	12.810	13.010
A1	1.240	1.340	1.440	E	9.900	10.000	10.100
A2	2.500	2.600	2.700	E1	8.240	8.440	8.640
b	0.740	0.840	0.940	E2	9.900	10.100	10.300
b1	0.700	0.800	0.900	e	2.540 BSC.		
b2	1.210	1.310	1.410	H1	6.000	6.200	6.400
b3	1.170	1.270	1.370	L	13.140	13.340	13.540
c	0.440	0.540	0.640	L1	3.385	3.585	3.785
c1	0.400	0.500	0.600	ØP	3.740	3.840	3.940
D	9.100	9.200	9.300	Q	2.600	2.740	2.940
D1	15.200	15.400	15.600	R	0.108 REF.		