P-Channel Enhancement Mode Power MOSFET

Description

The G2K6P25TA uses advanced trench technology to provid e excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.

AEC-Q101Qualified

General Features

- V_{DS} -250V
- I_D (at V_{GS} = -10V) -28A
- $R_{DS(ON)}$ (at V_{GS} = -10V) < 260mΩ
- 100% Avalanche Tested
- RoHS Compliant

Application

- Power switch
- DC/DC converters



Schematic diagram



TO-220

PRELIMINARY

Ordering Information

Device	Package	Marking	Packaging
G2K6P25TA	TO-220	G2K6P25	50pcs/Tube

Absolute Maximum Ratings T_C = 25ºC, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-250	V
Continuous Drain Current	I_D	-28	A
Pulsed Drain Current (note1)	I_{DM}	-112	A
Gate-Source Voltage	V_{GS}	±20	V
Power Dissipation	P_D	300	W
Single pulse avalanche energy （note2）	E_{AS}	110	mJ
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	ºC

Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	62.5	ºC/W
Maximum Junction-to-Case	R_{thJC}	0.42	ºC/W

Specifications T_J = 25ºC, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = -250μA	-250	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -250V, V_{GS} = 0V	--	--	-1	μA
Gate-Source Leakage	I_{GSS}	V_{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250μA	-2.0	-3.0	-4.0	V
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS} = -10V, I_D = -10A	--	215	260	mΩ
Forward Transconductance	g_{FS}	V_{DS} = -5V,I_D = -10A	--	11	--	S
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -125V, f = 1.0MHz	--	2984	--	pF
Output Capacitance	C_{oss}		--	85	--	
Reverse Transfer Capacitance	C_{rss}		--	60	--	
Total Gate Charge	Q_g	V_{DD} = -125V, I_D = -10A, V_{GS} = -10V	--	77	--	nC
Gate-Source Charge	Q_{gs}		--	25	--	
Gate-Drain Charge	Q_{gd}		--	21	--	
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = -125V, I_D = -10A, R_G = 6Ω	--	14	--	ns
Turn-on Rise Time	t_r		--	14	--	
Turn-off Delay Time	$t_{d(off)}$		--	111	--	
Turn-off Fall Time	t_f		--	51	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	T_C = 25ºC	--	--	-28	A
Body Diode Voltage	V_{SD}	T_J = 25ºC, I_{SD} = -10A, V_{GS} = 0V	--	--	-1.2	V
Reverse Recovery Charge	Q_{rr}	I_F = -10A, V_{GS} = 0V di/dt=-100A/us	--	87	--	nC
Reverse Recovery Time	T_{rr}		--	48	--	ns

PRELIMINARY

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition : Tj=25℃ ,VDD=-50V,VGS=-10V,L=0.5mH,Rg=25Ω
   The table shows the minimum avalanche energy, which is 306mJ when the device is tested until failure
3. Identical low side and high side switch with identical R_G

Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



PRELIMINARY

Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3.Drain Source On Resistance



Figure 4. Gate Charge



Figure 5. Capacitance



Figure 6. Source-Drain Diode Forward



PRELIMINARY

Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 7. Drain-Source On-Resistance



Figure 10. Safe Operation Area



Figure 9. Normalized Maximum Transient Thermal Impedance



PRELIMINARY

TO-220 Package Information



PRELIMINARY

COMMON DIMENSIONS

SYMBOL	mm		
	MIN	NOM	MAX
A	4.37	4.57	4.77
A1	1.22	1.27	1.42
A2	2.49	2.69	2.89
b	0.75	0.81	0.96
b2	1.22	1.27	1.47
c	0.30	0.38	0.48
D1	8.50	8.70	8.90
D2	5.20	–	–
E	9.86	10.16	10.36
E5	7.06	–	–
e	2.54BSC		
e1	5.08BSC		
H1	6.10	6.30	6.50
L	13.10	13.40	13.70
L1	–	3.75	4.10
ΦP	3.70	3.84	3.99
Q	2.54	2.74	2.94