P-Channel Enhancement Mode Power MOSFET

Description

The G70P04K uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.

General Features

- V_{DS} -40V
- I_D (at V_{GS} = -10V) -70A
- $R_{DS(ON)}$ (at V_{GS} = -10V) < 10mΩ
- $R_{DS(ON)}$ (at V_{GS} = -4.5V) < 12mΩ
- 100% Avalanche Tested
- RoHS Compliant

Application

- Power switch
- DC/DC converters



Schematic diagram



TO-252

Ordering Information

Device	Package	Marking	Packaging
G70P04K	TO-252	G70P04	2500pcs/Reel

Absolute Maximum Ratings T_C = 25ºC, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-40	V
Continuous Drain Current	I_D	-70	A
Pulsed Drain Current (note1)	I_{DM}	-280	A
Gate-Source Voltage	V_{GS}	±20	V
Power Dissipation	P_D	88	W
Single pulse avalanche energy （note3）	E_{AS}	169	mJ
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	ºC

Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	50	ºC/W
Maximum Junction-to-Case	R_{thJC}	1.42	ºC/W

Specifications T_J = 25ºC, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = -250μA	-40	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -40V, V_{GS} = 0V	--	--	-1	uA
Gate-Source Leakage	I_{GSS}	V_{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250μA	-1.0	-1.4	-2.5	V
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS} = -10V, I_D = - 10A	--	7	10	mΩ
		V_{GS} = -4.5V, I_D = - 8A	--	9	12	
Forward Transconductance	g_{FS}	V_{DS} = -5V,I_D = -20A	--	58	--	S
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -20V, f = 1.0MHz	--	4714	--	pF
Output Capacitance	C_{oss}		--	446	--	
Reverse Transfer Capacitance	C_{rss}		--	456	--	
Total Gate Charge	Q_g	V_{DD} = -20V, I_D = -10A, V_{GS} = -10V	--	42	--	nC
Gate-Source Charge	Q_{gs}		--	7	--	
Gate-Drain Charge	Q_{gd}		--	9.5	--	
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = -20V, I_D = -10A, R_G = 3Ω	--	10	--	ns
Turn-on Rise Time	t_r		--	18	--	
Turn-off Delay Time	$t_{d(off)}$		--	38	--	
Turn-off Fall Time	t_f		--	24	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	T_C = 25ºC	--	--	-26	A
Body Diode Voltage	V_{SD}	T_J = 25ºC, I_{SD} = -8A, V_{GS} = 0V	--	--	-1.2	V
Reverse Recovery Time	T_{rr}	I_S = -10A, V_{GS} = 0V di/dt=-100A/us	--	40	--	ns
Reverse Recovery Charge	Qrr		--	42	--	ns

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition : Tj=25℃ ,VDD=40V,VGS=10V,L=0.5mH,Rg=25Ω
3. Identical low side and high side switch with identical R_G

Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Gate Charge



Figure 4. Drain Source On Resistance



Figure 5. Capacitance



Figure 6. Source-Drain Diode Forward



Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 7. Drain-Source On-Resistance



Figure 8. Safe Operation Area



Figure 9. Normalized Maximum Transient Thermal Impedance



TO-252 Package Information



Symbol	Dimensions in Millimeters		
	MIN.	NOM.	MAX.
A	2.2	2.3	2.4
A1	0		0.2
A2	0.97	1.07	1.17
b	0.68	0.78	0.9
b3	5.2	5.33	5.5
c	0.43	0.53	0.63
D	5.98	6.1	6.22
D1	5.30REF		
E	6.4	6.6	6.8
E1	4.63		
e	2.286BSC		
H	9.4	10.1	10.5
L	1.38	1.5	1.75
L1	2.90REF		
L2	0.51BSC		
L3	0.88		1.28
L4	0.5		1
L5	1.65	1.8	1.95
θ	0°		8°