N-Channel Enhancement Mode Power MOSFET

Description

The GT095N04D5A uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.

AEC-Q101 Qualified

General Features

- V_{DS} 40V
- I_D (at V_{GS} = 10V) 54A
- $R_{DS(ON)}$ (at V_{GS} = 10V) < 6mΩ
- $R_{DS(ON)}$ (at V_{GS} = 4.5V) < 9.5mΩ
- 100% Avalanche Tested
- RoHS Compliant

Application

- Power switch
- DC/DC converters



Schematic diagram



pin assignment



DFN5X6-8L

Ordering Information

Device	Package	Marking	Packaging
GT095N04D5A	DFN5X6-8L	GT095N04	5000pcs/Reel

Absolute Maximum Ratings T_C = 25ºC, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	40	V
Continuous Drain Current	I_D	54	A
Pulsed Drain Current (note1)	I_{DM}	216	A
Gate-Source Voltage	V_{GS}	±20	V
Power Dissipation	P_D	29.8	W
Single pulse avalanche energy （note2）	E_{AS}	25	mJ
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	ºC

Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	50	ºC/W
Maximum Junction-to-Case	R_{thJC}	4.2	ºC/W

Specifications T_J = 25ºC, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA	40	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 40V, V_{GS} = 0V	--	--	1	μA
Gate-Source Leakage	I_{GSS}	V_{GS} = ±20V	--	--	±100	nA
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250μA	1.0	1.6	2.5	V
Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS} = 10V, I_D = 10A	--	5.0	6.0	mΩ
		V_{GS} = 4.5V, I_D = 10A	--	7.8	9.5	
Forward Transconductance	g_{FS}	V_{GS} = 5V, I_D = 10A	--	37	--	S
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = 20V, f = 1.0MHz	--	942	--	pF
Output Capacitance	C_{oss}		--	214	--	
Reverse Transfer Capacitance	C_{rss}		--	213	--	
Total Gate Charge	Q_g	V_{DD} = 20V, I_D = 10A, V_{GS} = 10V	--	23	--	nC
Gate-Source Charge	Q_{gs}		--	4.5	--	
Gate-Drain Charge	Q_{gd}		--	4	--	
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = 20V, I_D = 10A, R_G = 1.6Ω	--	8	--	ns
Turn-on Rise Time	t_r		--	3.5	--	
Turn-off Delay Time	$t_{d(off)}$		--	30	--	
Turn-off Fall Time	t_f		--	4	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	T_C = 25ºC	--	--	54	A
Body Diode Voltage	V_{SD}	T_J = 25ºC, I_{SD} = 10A, V_{GS} = 0V	--	--	1.2	V
Reverse Recovery Charge	Qrr	I_F = 10A, V_{GS} = 0V di/dt=100A/us	--	25	--	nC
Reverse Recovery Time	Trr		--	14	--	ns

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition : Tj=25℃ ,VDD=40V,VGS=10V,L=0.5mH,Rg=25Ω
3. Identical low side and high side switch with identical R_G

Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Drain Source On Resistance



Figure 4. Gate Charge



Figure 5. Capacitance



Figure 6. Source-Drain Diode Forward



Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 7. Drain-Source On-Resistance



Figure 8. Safe Operation Area



Figure 9. Normalized Maximum Transient Thermal Impedance



DFN5X6-8L Package Information



	SYMBOL	COMMON			
		MM		INCH	
		MIN.	MAX.	MIN.	MAX.
	A	1.03	1.17	0.0406	0.0461
	b	0.34	0.48	0.0134	0.0189
	c	0.824	0.970	0.0324	0.0382
3	D	4.80	5.40	0.1890	0.2126
	D1	4.11	4.31	0.1618	0.1697
3	D2	4.80	5.00	0.1890	0.1969
	E	5.95	6.15	0.2343	0.2421
	E1	5.65	5.85	0.2224	0.2303
5	E2	1.40	—	0.0551	—
	e	1.27 BSC		0.05 BSC	
3	L	0.05	0.25	0.0020	0.0098
	L1	0.38	0.50	0.0150	0.0197
5	L2	0.38	0.71	0.0150	0.0280
4	H	3.30	3.50	0.1299	0.1378
	I	—	0.18	—	0.0070